



www.wash-water-treatment.com

- Wash Water Recycling and Treatment Systems
- Detergent • Accessories • Replacement parts

PSM

Pressurization Supply Module

PSM: Automated Pressurization Supply Modules

The PSM Pressurization Supply Module systems are provided to store treated water and supply it back to the pressure washer(s) under pressure on demand and supply to the Mud Blaster supply pump. The PSM systems are offered in a range of flow rates from 5 to 50 GPM with larger systems available. The PSM consist of the following components:

- Clean water storage tank
- Pressurization pump, stainless steel construction
- Hydro-pneumatic tank to maintain line pressure
- Pressure switch to maintain automatic pressure control
- Clean water tank low level sensor to protect pump against lose of water supply
- Automatic controls

The PSM can be used as a stand-alone collection and supply system or retro-fit to an existing system.

The storage tank can be provided per the standard volumes or we can provide larger volumes to fit your facility needs.



PSM Equipment Detail			
Model	Flow Rate GPM	Tank Volume	Voltage V/pH/Hz
PSM-3.5-300	3-5	300 g	115/1/60
PSM-5.8-300	5-8	300	115/1/60
PSM-8.10-300	8-10	300	115/1/60
PSM-10.15-500	10-15	500	230/3/60
PSM-15.25-500	15-25	500	230/3/60
Tank Dimensions			
300 gallon	36"D X 77"H		
500 gallon	48"D X 72"H		
Pump Skid Dims	30"L X 43"W X 37"H		

PSM Alternate Clean Water Storage Tanks			
Model	Volume Gal.	Oper. Weight	Dimensions Dia X H
CWS-1000-P	1000	8,740	64" X 80"
CWS-1500-P	1500	13,175	64" X 116"
CWS-2000-P	2000	17,580	64" X 152"
MOC: HDPE			

950 N. Rand Rd., Ste 120 Wauconda, IL 60084 USA
847-487-9166 Fax: 847-487-9218

www.wash-water-treatment.com www.panamenv.com panam@panamenv.com

©1991-2014 Pan America Environmental, Inc.

